

| Traglastindex | kg | | Traglastindex | kg | | Traglastindex | kg |
|---------------|-----|--|---------------|------|--|------------------------------|-------------|
| 57 | 230 | | 89 | 580 | | 125 | 1650 |
| 58 | 236 | | 90 | 600 | | 130 | 1900 |
| 59 | 243 | | 91 | 615 | | 135 | 2180 |
| 60 | 250 | | 92 | 630 | | 140 | 2500 |
| 61 | 257 | | 93 | 650 | | 145 | 2900 |
| 62 | 265 | | 94 | 670 | | 150 | 3350 |
| 63 | 272 | | 95 | 690 | | 155 | 3875 |
| 64 | 280 | | 96 | 710 | | 160 | 4500 |
| 65 | 290 | | 97 | 730 | | | |
| 66 | 300 | | 98 | 750 | | | |
| 67 | 307 | | 99 | 775 | | | |
| 68 | 315 | | 100 | 800 | | | |
| 69 | 325 | | 101 | 825 | | Geschwindigkeitsindex | |
| 70 | 335 | | 102 | 850 | | Index | km/h |
| 71 | 345 | | 103 | 875 | | F | 80 |
| 72 | 355 | | 104 | 900 | | G | 90 |
| 73 | 365 | | 105 | 925 | | J | 100 |
| 74 | 375 | | 106 | 950 | | K | 110 |
| 75 | 387 | | 107 | 975 | | L | 120 |
| 76 | 400 | | 108 | 1000 | | M | 130 |
| 77 | 412 | | 109 | 1030 | | N | 140 |
| 78 | 425 | | 110 | 1060 | | P | 150 |
| 79 | 437 | | 111 | 1090 | | Q | 160 |
| 80 | 450 | | 112 | 1120 | | R | 170 |
| 81 | 462 | | 113 | 1150 | | S | 180 |
| 82 | 475 | | 114 | 1180 | | T | 190 |
| 83 | 487 | | 115 | 1215 | | U | 200 |
| 84 | 500 | | 116 | 1250 | | H | 210 |
| 85 | 515 | | 117 | 1285 | | V | 240 |
| 86 | 530 | | 118 | 1320 | | W | 270 |
| 87 | 545 | | 119 | 1360 | | Y | 300 |
| 88 | 560 | | 120 | 1400 | | Z | > 240 |

Alle Angaben ohne Gewähr